

A P O L L O TM

150W Round High Bay Light

- Housing: Die-cast aluminum
- Light engine thermally isolated from driver components
- UV stabilized polyester powder paint finish
- Rated Power: 150W
- IP Rating: IP65
- High efficiency driver, PF>.95
- 120° beam angle
- 100-277V (5000K)
- Warranty: 50,000 hours or 5 years
- 24' cable lead
- 1.8 AMP's
- 21,000 Lumens



Encased Ceramic Magnets With Threaded Stud

- (2) 200lb magnets securely attached to pivoting yoke mount, with adjustable finger knobs
- Max temperature 120°F
- Outside diameter: 3"
- Thickness: .76"
- Stud length: .87"
- Overall length: 1.63"
- Magnet Grade: C8
- Thread Size: 3/8"-16



Comfort Grip Knobs

- (2) Rubber coated polypropylene plastic
- Thread size: 3/8"-16
- Thread Dp: 1/2"
- Head diameter: 2 1/4"
- Head Height: 15/16"
- Insert Material: Zinc-plated brass
- Temperature Range: -15° to 210°



Magnetic Wire Clips

- Polycarbonate Plastic
- Max bundle size: 1/2"
- Holding Capacity: 10lbs
- Temperature Range: -40° to 170°



BOOMLIGHT.COM
888.202.0115 | info@boomlight.com